

## Application Instructions For Windshield Decal

### Materials required:

- Spray bottle with clean water with **2 drops of dish washing liquid added.**
- Razor blade or X-acto™ knife (for best results use a new blade)
- Ruler
- Small squeegee (a credit card will work)
- An Assistant

Application of these vinyl decals takes a little time and patience. Proceed slowly. Some custom fitting, positioning and cutting may be required for your vehicle. The use of the water spray allows for repositioning of the decal if required. Read the following instructions thoroughly before proceeding.

### Visor Decal (if applicable)

1. Clean the window of the car with a Windex™ type cleaner.
2. Spray the upper portion of the windshield area thoroughly with water.
3. Peel away the backing paper from the visor decal and spray the tacky side of the decal with water.
4. Have your assistant hold the other end of the decal and position it over the windshield. For best results, do not try and align the visor decal with the rubber moulding. Instead, allow the decal to slightly overlap the moulding (about 1/4-inch). This will allow you to custom trim your visor decal to fit your car exactly.
5. Make measurements to make certain your decal is centered and evenly placed. If you need to re-position your visor decal, pull the decal away gently from the car and re-position. Use more water if needed.
6. If you are satisfied with the visor position, use your squeegee to gently work out the water and air bubbles. Be careful not to crease or tear the visor decal. If you are not able to remove an air bubble, the bubble may be "popped" by using the end of the X-acto™ blade. Work the air and water out through the hole.
7. Carefully trim the edges of the visor decal. Proceed slowly, taking care not to cut into the rubber edge moulding.
8. Dry the decal with a soft, clean rag.

### Logo Decal

1. If the logo will be applied directly to the window, clean the window of the car with a Windex™ type cleaner. Trim the paper backing and overlay to about 1/4" from the top of the logo to aid in positioning.
2. Spray the upper portion of the windshield area thoroughly with water.
3. Peel away the backing paper from the logo decal (not the paper overlay) and spray the tacky side of the decal with water.
4. Have your assistant hold the other end of the decal and position it over the windshield. Position the logo decal over the windshield (or visor decal). Place the decal onto the car and slide it into place. Make measurements to make certain the logo is centered and evenly placed. If needed, make a series of "cuts" between the letters to aid in positioning. If you need to reposition your logo decal, pull the decal away gently from the car and reposition. Use more water if needed.
5. When you are satisfied with the logo decal position, use your squeegee to gently work out the water and air bubbles. Be careful not to crease or tear the logo decal. Now, spray the paper overlay with water and let the decal sit for a few minutes.
6. Squeegee out any remaining bubbles, then slowly remove the paper overlay. Work slowly to prevent the logo from pulling away from the windshield. If the logo does pull away, press the logo back into place.
7. Dry the decal with a soft rag. Do not wash the car for 24 hours. If any edges of your decal have lifted while drying, simply press them back into place.